

	CK-5134N	CK-5134P
Image sensor	1/4" Interline Transfer SONY Exview HAD CCD	
Signal system	NTSC	PAL
Picture elements	811(H) x 508(V)	795(H) x 596(V)
Scanning system	525lines, 2:1 interlace	625lines, 2:1 interlace
Sync system	Internal	
Horizontal resolution	540TV Lines	
Minimum illumination	0.1 lux at F1.6 (Color mode, 30 IRE, SAGC)/0.02 lux at F1.6 (B/W mode, 30 IRE, SAGC) 0.002 lux at F1.6 (64x sense up, 30 IRE, SAGC)/0 Lux under IR illumination	
Infrared wavelength	700nm to 1100nm	
OLPF switch level adj.	0.02 ~ 15 Lux adjustable	
OLPF switch delay time	5 ~ 8 sec	
Spherical auto tracking	24 areas spherical setting simulate with zoom in out	
Auto tracking activate	based on 1/48 area motion detected	
Auto tracking detected range	5-70 meter	
Masking setting	24 areas spherical setting simulate with zoom in out	
S/N ratio	Better than 50 dB	
White balance	ATW 2500°K ~ 9500°K Preset / Manual	
BLC function	Auto On/ Off, 48 areas and weighting adjustable	
Gamma correction	0.45	
AGC	Super AGC 0 ~ 36 dB	
Electronic shutter	1/50~1/100,000 sec	
Fixed shutter	1/100, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/10000	
Frame integration	2x ~ 64x sense up adjustable	
Optical zoom	23x optical zoom lens (F1.6 ~ 3.8, f=3.6 ~ 82.8mm)	
Digital zoom	10x digital zoom	
Zoom/focus/iris motors life	800,000 times	
Focus	Auto / Manual	
Video output	Composite output 10.v p-p at 75Ω□□	
Rotation mode	Auto Pan Feature / Preset Position Patrol / Auto-Flip	
Rotation angle	Horizontal Pan 0° ~ 375° / Vertical Tilt 0° ~ 95°	
Rotation speed	Horizontal Pan 400°/sec / Vertical Tilt 330° /sec	
Speed setting	Auto: Approx. 2.5~60/sec(Variable) / Manual: Approx. 2.5~160/sec(Variable) / Preset: Max. 320/sec	
Stop times	5 ~ 255 Sec (Variable)	
Alarm inputs	4 inputs	
Alarm outputs	1 output	
Preset	62 Points	
Control	Infrared Remote Control + RS-485 Control	
Max link	256 Cameras	
Protocol	PELCO-D 2400, PELCO-P 4800, PELCO-P 9600,DYNA 9600, ELITAR 2400, CHIPER 9600, LILIN 9600.	
Power supply	DC13.5V / 2.2A	
Power Consumption	2A	
Ambient Operation	-30 ~ 60 / 20% ~ 90% RH	
Blower / Heater	Blower: On40 ,Off 30 Heater: On -5	
Installation location	Indoor / Outdoor,Ceiling mountedWall mounted withGooseneck Bracket	
Dimensions	Ø217 x H175 mm	
Weight	3.4Kg	
Weather Proof Ratio	IP66	